




MATERIAL SAFETY DATA SHEET

LeakBarrier™ Products

DOOR AND WINDOW TAPE



Manufacturer TARCO SPECIALTY PRODUCTS, INC.		Identity (Trade Name As Used On Label)
Address One Information Way Suite 225		MSDS Number 0108
LITTLE ROCK, AR 72202		CAS Number NONE
Phone Number (For Information) 501-945-4506		Date Prepared: 12/22/03 Revised:
Emergency Phone Number 254-939-3775		Prepared By D. RAINS

SECTION 1 – MATERIAL IDENTIFICATION AND INFORMATION

Exposure Limits

	Cas Reg. #	%	OSHA TWA	ACGIH TWA	FORM
Petroleum Asphalt Flux	8052-42-4	40-60	5mg/m ³	5mg/m ³	Fume
Styrene Butadiene Block Co-Polymer	9003-55-8	10-20	NA	NA	
Mineral Oil	64741-96-4	3-8	5mg/m ³	5mg/m ³	Mist
Limestone	1317-65-3	5-15	15mg/m ³	10mg/m ³	Respirable Particulate

NA=Not Applicable

Due to form, exposure to dusts and fumes is not expected to occur. Exposure limits are given for reference only.

SECTION 2 PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	Not Determined	Specific Gravity (H ₂ O = 1)	Not Determined
Vapor Pressure (mm Hg and Temperature)	N/A	Melting Point	>180°F
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	INSOLUBLE	Water Reactive	N/A

Appearance and Odor:
Black pliable solid, rubber and petroleum odor.

SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method Used >500F, COC	Auto-Ignition Temperature >750°F	Flammability Limits in Air % by Volume N/A	LEL N/A	UEL N/A
Extinguisher Media FOAM, CO ₂ , DRY CHEMICAL, HALON – AVOID USE OF STRAIGHT STREAM WATER				
Special Fire Fighting Procedures WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING				
Unusual Fire and Explosion Hazards - WHEN HEATED, FUMES MAY BURN IF AN IGNITION SOURCE IS PROVIDED. FUMES MAY EXPLODE IF EMITTED IN AN ENCLOSED ENVIRONMENT WITH AN IGNITION SOURCE.				

SECTION 4 – REACTIVITY HAZARD DATA

STABILITY	Stable <input checked="" type="checkbox"/> Unstable <input type="checkbox"/>	Conditions To Avoid N/A
Incompatibility (Materials to Avoid)	STRONG ACIDS OR BASES, OXIDIZING AGENTS	
Hazardous Decomposition Products	CO, CO2, OZONE, HYDROGEN SULFIDE, OXIDES OF SULFUR AND VARIOUS HYDROCARBON	
HAZARDOUS POLYMERIZATION – WILL NOT OCCUR		

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: <input type="checkbox"/> Inhalation <input type="checkbox"/> Skin Absorption <input checked="" type="checkbox"/> Ingestion <input checked="" type="checkbox"/>	CARCINOGEN LISTED IN: <input type="checkbox"/> NTP <input type="checkbox"/> IARC Monograph <input type="checkbox"/> OSHA <input checked="" type="checkbox"/> Not Listed
HEALTH	Acute MECHANICAL IRRITATION
HAZARDS	Chronic DUE TO PRODUCT FORM AND RECOMMENDED USE, EXPOSURES TO DUSTS OR FUMES ARE NOT EXPECTED
Signs and Symptoms of Exposure	N/A
Medical Conditions Generally Aggravated by Exposure	N/A
EMERGENCY FIRST AID PROCEDURES	- SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT IF NECESSARY.
Eye Contact	- IF PARTICLES ENTER THE EYE, IT WILL CAUSE IRRITATION POSSIBLY RESULTING IN STARCHING OF THE EYE, STINGING, REDNESS OR SWELLING.
Skin Contact	- PRIMARY ROUTE OF EXPOSURE IS SKIN CONTACT. REPEATED CONTACT MAY CAUSE TEARING OF SKIN, REDNESS, DRYING OR CRACKING.
Inhalation	- IF PRODUCT IS HEATED, EXPOSURE TO FUMES, VAPORS OR MISTS MAY CAUSE IRRITATION OF THE NOSE AND THROAT. USE OF PRODUCT IN WELL-VENTILATED WORKING AREAS IS NOT EXPECTED TO CAUSE ADVERSE EFFECTS.
Ingestion	- TYPICALLY APSHALT PRODUCTS HAVE LOW TOXICITY WHEN SWALLOWED. IF SWALLOWED THIS PRODUCT MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT FOLLOWED BY VOMITING. SHOULD VOMITING OCCUR, SMALL AMOUNTS OF MATERIAL CAN BE ASPIRATED INTO THE LUNG.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type)	IF IRRITATION OCCURS, USE 3M-9900 OR 3m-8710 OR EQUIVALENT	
Protective Gloves	RECOMMENDED TO PREVENT ABRASION OR SKIN IRRITATION	Eye Protection SAFETY GLASSES WITH SIDE SHIELDS
VENTILATION	<input checked="" type="checkbox"/> Local Exhaust AMBIENT	<input type="checkbox"/> Mechanical (General) N/A
TO BE USED	<input type="checkbox"/> Special N/A	<input checked="" type="checkbox"/> Other (Specify) MECHANICAL IN CONFINED SPACES IF MATERIAL IS HEATED
Other Protective Clothing and Equipment	N/A	
Hygienic Work Practices	WASH HANDS AFTER APPLICATION	

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

Steps to be Taken if Material is Spilled or Released	PICK UP PIECES AND DISPOSE PROPERLY. AVOID DRY SWEEPING OR BLOWING WITH AIR IN CONFINED SPACES.
Waste Disposal Methods	DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS
Precautions to be Taken in Handling and Storage	STORE AWAY FROM HEAT AND ALL IGNITION SOURCES AND OPEN FLAMES.
Other Precautions and/or Special Hazards	N/A